

Appl. No. 10/604,916
 Amdt. dated October 11, 2004
 Reply to Office action of August 12, 2004

Amendments to the Claims:

The listing of claims will replace all prior versions and listings of claims in the application:

5 Listing of Claims:

- Claim 1 (currently amended) A portable dryer comprising:
- a housing with an opening at one end thereof;
 - a motor having a fan installed inside the housing;
 - a first heating filament coupled to the motor;
 - 10 a second heating filament coupled to the motor and the first heating filament;
 - a third heating filament;
 - a fourth heating filament coupled to the third heating filament;
 - a switch for controlling operations of the portable dryer; and
 - 15 a power unit for supplying electric power;
- wherein the power unit is electrically ~~disconnected from~~ disconnected from the motor and all electric heating filaments ~~when the switch~~ when the switch is turned to an off position, the motor is electrically connected to the first heating filament in series and then to the third heating filament in parallel
- 20 when the switch is turned to a first operation position, and both the first heating filament and the second heating filament ~~are~~ filament are electrically connected in parallel and electrically ~~connected to~~ connected to the motor in series and then to both the ~~third heating filament and~~ third heating filament and the fourth heating filament in parallel when the switch
- 25 is turned to a second operation position.

Claim 2 (currently amended) The portable dryer of claim 1, wherein when the switch is turned to the first operation position, the second heating filament and filament and the fourth heating filament ~~are electrically~~

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

~~disconnected from~~ filament are electrically disconnected from the power unit.

- 5 Claim 3 (currently amended) The portable dryer of claim 1, wherein the switch comprises a conductor and a plurality of connecting nodes, the conductor able to establish electrical ~~connections among~~ connections among the plurality of connecting nodes so that the power unit is electrically disconnected from the motor and the heating filaments, or
10 electrically connected with both the motor and the third heating filament, or electrically connected with the motor, the third heating filament, and the fourth heating filament.

- Claim 4 (currently amended) The portable dryer of claim 3, wherein the
15 conductor is ~~rotatably installed~~ rotatably installed to establish electrical ~~connections among~~ connections among the plurality of connecting nodes.

- Claim 5 (Original) The portable dryer of claim 3, wherein the conductor is shiftable to establish electrical connections among the plurality of
20 connecting nodes.

Claim 6 (Original) The portable dryer of claim 3, wherein the switch is a push-button switch.

- 25 Claim 7 (currently amended) The portable dryer of claim 1 further comprising a transformer electrically connected to ~~the power~~ the power unit for boosting an outputted voltage level of the power unit.

Claim 8 (Original) The portable dryer of claim 1 further comprising an

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

overload protection device electrically connected to the power unit for preventing damage to the portable dryer.

5

Claim 9 (currently amended) A portable dryer comprising:

a housing with an opening at one end thereof;

a motor having a fan installed inside the housing;

a first heating filament coupled to the motor;

10 a second heating filament coupled to the motor and the first heating filament;

a third heating filament;

a fourth heating filament coupled to the third heating filament;

a switch for controlling operations of the portable dryer; and

15 a power unit for supplying electric power;

wherein the power unit is electrically ~~disconnected from~~ disconnected from the motor and all electric heating filaments ~~when~~ filaments when the switch is turned to an off position, the motor is electrically connected to the first heating filament in series and then to the third heating filament in parallel
20 when the switch is turned to a first operation position, and the first heating filament is electrically ~~disconnected to~~ disconnected to the power unit ~~and~~ unit and the motor is electrically connected to the second heating filament in series and then to the ~~third heating filament and~~ third heating filament and the fourth heating filament in parallel when the switch is turned to a
25 second operation position.

Claim 10 (currently amended) The portable dryer of claim 9, wherein when the switch is turned to the first operation position, the second heating filament ~~and~~ filament and the fourth heating filament ~~are electrically~~

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

~~disconnected from~~ filament are electrically disconnected from the power unit.

5

Claim 11 (currently amended) The portable dryer of claim 9, wherein the switch comprises a conductor and a plurality of connecting nodes, the conductor able to establish electrical ~~connections among~~ connections among the plurality of connecting nodes so that the power unit is
10 electrically disconnected from the motor and the heating filaments, or electrically connected with both the motor and the third heating filament, or electrically connected with the motor, the third heating filament, and the fourth heating filament.

15 Claim 12 (currently amended) The portable dryer of claim 11, wherein the conductor is ~~rotatably installed~~ rotatably installed to establish electrical ~~connections among~~ connections among the plurality of connecting nodes.

Claim 13 (Original) The portable dryer of claim 11, wherein the
20 conductor is shiftable to establish electrical connections among the plurality of connecting nodes.

Claim 14 (Original) The portable dryer of claim 11, wherein the switch is a push-button switch.

25

Claim 15 (Original) The portable dryer of claim 9 further comprising a transformer electrically connected to the power unit for boosting an outputted voltage level of the power unit.

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

Claim 16 (Original) The portable dryer of claim 9 further comprising an
overload protection device electrically connected to the power unit for
5 preventing damage to the portable dryer.

Claim 17 (currently amended) A portable dryer comprising:
a housing with an opening at one end thereof;
a motor having a fan installed inside the housing;
10 a first heating filament coupled to the motor;
a second heating filament coupled to the motor and the first heating
filament;
a third heating filament;
a fourth heating filament coupled to the third heating filament;
15 a switch for controlling operations of the portable dryer; and
a power unit for supplying electric power;
wherein the power unit is electrically ~~disconnected from~~ disconnected from
the motor and all electric heating filaments ~~when~~ filaments when the switch
is turned to an off position, the motor is electrically connected to the first
20 heating filament in series and then to the third heating filament in parallel
when the switch is turned to a first operation position, and the third heating
filament is electrically ~~disconnected to~~ disconnected to the power unit
~~and both~~ and both the first heating filament and the second heating
filament ~~are~~ filament are connected in parallel and electrically connected to
25 the motor in series and then to the fourth heating filament in parallel when
the switch is turned to a second operation position.

Claim 18 (currently amended) The portable dryer of claim 17, wherein
when the switch is turned to the first operation position, the second heating

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

~~filament and filament and~~ the fourth heating filament are electrically
disconnected from filament are electrically disconnected from the power
5 unit.

Claim 19 (currently amended) The portable dryer of claim 17, wherein the
switch comprises a conductor and a plurality of connecting nodes, the
10 conductor able to establish electrical ~~connections among~~ connections
among the plurality of connecting nodes so that the power unit is
electrically disconnected from the motor and the heating filaments, or
electrically connected with both the motor and the third heating filament,
or electrically connected with both the motor and the fourth heating
15 filament.

Claim 20 (currently amended) The portable dryer of claim 19, wherein the
conductor is ~~rotatably installed~~ rotatably installed to establish electrical
~~connections among~~ connections among the plurality of connecting nodes.
20

Claim 21 (Original) The portable dryer of claim 19, wherein the conductor
is shiftable to establish electrical connections among the plurality of
connecting nodes.

25 Claim 22 (Original) The portable dryer of claim 19, wherein the switch is a
push-button switch.

Claim 23 (Original) The portable dryer of claim 17 further comprising a
transformer electrically connected to the power unit for boosting an

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

outputted voltage level of the power unit.

- 5 Claim 24 (Original) The portable dryer of claim 17 further comprising an overload protection device electrically connected to the power unit for preventing damage to the portable dryer.

Claim 25 (currently amended) A portable dryer comprising:

- 10 a housing with an opening at one end thereof;
a motor having a fan installed inside the housing;
a first heating filament coupled to the motor;
a second heating filament coupled to the motor and the first heating filament;
15 a third heating filament;
a fourth heating filament coupled to the third heating filament;
a switch for controlling operations of the portable dryer; and
a power unit for supplying electric power;
wherein the power unit is electrically ~~disconnected from~~ disconnected from
20 the motor and all electric heating filaments ~~when~~ filaments when the switch is turned to an off position, the motor is electrically connected to the first heating filament in series and then to the third heating filament in parallel when the switch is turned to a first operation position, and the ~~first heating filament and~~ first heating filament and the third heating
25 filament ~~are electrically disconnected to~~ are electrically disconnected to the power ~~unit and~~ unit and the motor is electrically connected to the second heating filament in series and then to the fourth heating filament in parallel when the switch is turned to a second operation position.

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

Claim 26 (currently amended) The portable dryer of claim 25, wherein
when the switch is turned to the first operation position, the second heating
5 ~~filament and~~ filament and the fourth heating ~~filament are~~ electrically
~~disconnected from~~ filament are electrically disconnected from the power
unit.

Claim 27 (currently amended) The portable dryer of claim 25, wherein the
10 switch comprises a conductor and a plurality of connecting nodes, the
conductor able to establish electrical ~~connections among~~ connections
among the plurality of connecting nodes so that the power unit is
electrically disconnected from the motor and the heating filaments, or
electrically connected with both the motor and the third heating filament,
15 or electrically connected with both the motor and the fourth heating
filament.

Claim 28 (currently amended) The portable dryer of claim 27, wherein the
conductor is ~~rotatably installed~~ rotatably installed to establish electrical
20 ~~connections among~~ connections among the plurality of connecting nodes.

Claim 29 (Original) The portable dryer of claim 27, wherein the conductor
is shiftable to establish electrical connections among the plurality of
connecting nodes.

25

Claim 30 (Original) The portable dryer of claim 27, wherein the switch is a
push-button switch.

Claim 31 (Original) The portable dryer of claim 25 further comprising a

Appl. No. 10/604,916
Amdt. dated October 11, 2004
Reply to Office action of August 12, 2004

transformer electrically connected to the power unit for boosting an
outputted voltage level of the power unit.

5

Claim 32 (Original) The portable dryer of claim 25 further comprising an
overload protection device electrically connected to the power unit for
preventing damage to the portable dryer.

10